

DPS

Dried Parts Stabilizer

A stabilizing end coating for dried wood. DPS (Dried Parts Stabilizer) is a water-based, wax-less, semi-permeable coating that protects dried wood parts during storage and shipment.

THE BENEFITS OF DPS

- Reduces end splits and glue joint failure in dried wood parts
- Prevents post production shrinkage and swelling caused by humidity

APPLICATION, COVERAGE & USE

- DPS can be brushed or sprayed onto dried wood end grain.
- One gallon covers approximately 300-500 square feet, depending upon application method.

DIRECTIONS FOR USE

DPS is intended for use on rough dimension stock and panels. It should not be used on finished wood products or just prior to a staining or finishing process. End grain surface must be clean and free of loose particulate.

- **Equipment:** DPS can be applied with a brush, roller, or with spraying equipment. HVLP or airless sprayers are best.
- **Application:** Apply a thin, even coat. Do not over-apply or allow coating to pool on surfaces.
- **Clean-Up:** Use hot, soapy water to clean equipment. Solvent cleaners are not recommended or needed.

PURCHASE OPTIONS

- **Pricing information:** Please refer to the **U·C Coatings Product Price List (US & Canada)**
- **Place an order:**

US/CN Toll Free: **1-888-END-COAT**
Outside US/CN: **+1 (716) 833-9366**
On the Web: **www.uccoatings.com**



U·C COATINGS CORPORATION

"We're more than just end coatings"

PO Box 1066
Buffalo, NY 14215, USA
tel: 1 (716) 833-9366
fax: 1 (716) 833-0120
1-888-END-COAT
www.uccoatings.com